

# e-Cruise

## Installation instructions for Toyota Avensis & Verso models 2009 >

Signals on CAN: Brake - RPM - VSS



If the vehicle is equipped with automatic transmission:

The E-Cruise must be programmed.

See last page. "Test 6 - Setup to Automatic gear",  
or order Partno. 1609500 and download Android App "Cruise Toolbox".

## Before installation.

To make the installation easier, the complete installation instruction should be read through, before the installation is started.

This installation instruction, contains information, how to install the E-Cruise, which is not a Do-It-Yourself job.

Modern cars are equipped with electronic, which can be costly damaged by inappropriate treatment.

Lindgaard · Pedersen A/S can not be held responsible, for any error caused by wrong installation.

### Check that all the parts are included in the kit.



- 1 pcs. Unit.
- 1 pcs. 14-p connector.
- 1 pcs. 8-p connector.
- 1 pcs. 2-p connector for OBD.
- 1 pcs. Universal LED.
- 5 pcs. Cables.
- 1 pcs. Screws for the switch.
- 1 pcs. Installation guide.
- 1 pcs. Owners manual.

### Genuine parts required is not available from EL-PAS.

- 1 pcs. 84632-05010 Switch.
- 1 pcs. 84633-48020 Wire.
- 1 pcs. 45186-05020-C0 Cover.

### Some good advice.



- Always disconnect the negativ cable from the battery, before installing.
- Always use the enclosed installation instruction for installing the E-Cruise.
- The rev. number on the unit label and the installation guide must be the same.
- Be aware that eg. radio code might has to be typed in.
- Find a location to install the unit and control switch.
- If any wire(s) left, then cut off and insulate.
- Only use multimeter to measure.
- Always drive the car for a complete test, before assemble the car.
- Flying lead(s) must be soldered.
- All wire connections are viewed from wire side.




Dismount the originale OBD connector from the bracket, and connect the enclosed Y cable. Mount the other end of the Y cable in the bracket.



\* Cut off the side guides from the connector on the pedal and the Plug'n Play harness. (Remove the pedal, for better access).



Cut the Blue wire and solder the White/Purple wire from the E-Cruise onto the wire pointing against the connector.  
Solder the Black wire from the E-Cruise onto the Brown wire.



Disconnect the airbag in the manner prescribed by TOYOTA



**Toyota Avensis:**

Remove the cover on the right side. Mount the connector for the lever, and install the lever with the two enclosed 5mm screws. Mount the connector from the lever, in the 4-pole connector in the clock spring. (See Fig. 1). Mount the new enclosed cover. (Do not use the drill template).

**Toyota Verso:**

Remove the steering wheel and disassemble the steering wheel, so the plastic part is free. Cut the template after the lines, mount it on the right side of the steering wheel, after the marked edge on the plastic part. Use a 28mm drill. (See Fig. 2). Mount the connector for the lever, and install the lever with the two enclosed 5mm screws. Mount the connector from the lever, in the 4-pole connector in the clock spring. (See Fig. 1).

Remount the airbag.




## Trouble shooting guide.

### Enable Diagnostic mode:



Put ignition on the vehicle



Within 2 seconds, press and hold the ON function




Wait until test LED lights up in RED color



Release ON function



Within 5 seconds



Activate SET function briefly



The test LED lights up in ORANGE color



Within 5 seconds



Activate RES function briefly



The test LED will flash in all 3 colors.  
Continue the test according to the right.

Reaction to the individual tests, requires that the function is active

**Test 1 - Brake function. Activate RES briefly. Test LED will flash orange 1 time.**

**CANbus installation:** (No wires mounted on the brake connector).

1. Test LED lights up Red, and changes to green when pedal is depressed.

**Analog installation:** (Wires mounted on the brake connector).

1. If both brake wires are installed correctly, the test LED will light up green.
2. Hot side of brake is defective = test LED lights up red.
3. Cold side of brake is defective = test LED lights up orange.
4. Both sides of brake defective = test LED flashes all 3 colors.
5. When brake pedal is depressed, the test LED lights up orange.

**Test 2 - Clutch function. Activate RES briefly. Test LED will flash orange 2 times.**

**CANbus installation:** (No wires mounted on the clutch connector).

1. Test LED lights up Red, and changes to green when pedal is depressed.

**Analog installation:** (Wires mounted on the clutch connector).

1. If clutch wires are installed correctly, the test LED lights up green.
2. If clutch is defective, the test LED lights up red.
3. When clutch pedal is depressed, the test LED lights up red.

**Test 3 - Accelerator pedal function (engine off). Activate RES briefly. Test LED will flash orange 3 times.**

1. The test LED will slowly flash red/green.
2. Depressing the accelerator pedal will increase the freq. of the flashing.

**Test 4 - VSS function (engine running). Activate RES briefly. Test LED will flash orange 4 times.**

**CANbus installation:** (Purple wire is not connected).

1. The test LED will flash green if correct ID is received.

**Analog installation:** (Purple wire is connected).

1. The test LED will flash green when vehicle is moved.

**Test 5 - TACHO function (engine running). Activate RES briefly. Test LED will flash orange 5 times.**

**CANbus installation:** (Purple wire is not connected).

1. The test LED will flash green if correct ID is received.

**Analog installation:** (Purple wire is connected).

1. The test LED will flash green when RPM is raised.

**Test 6 - Setup to Automatic gear. Activate RES briefly. Test LED will flash orange 6 times.**

**(This point should ONLY be performed if it is described on the front page with red text).**

1. Activate and hold down the brake pedal.
2. Activate SET briefly = test LED lights up red.
3. Activate SET briefly again = test LED lights up orange. E-Cruise is set for automat gear.  
If this function is activated by mistake. The test procedure must be entered from start.

**Setup to Manual gear.**

1. Activate and hold down the brake pedal.
2. Activate SET briefly = test LED lights up green.
3. Activate SET briefly again = test LED lights up orange. E-Cruise is set for manual gear.